



		Dicke in mm „s“ Thickness in mm „s“											
		5	6	8	10	12	15	20	25	30	40	50	60
Breite mm „b“ width mm „b“	zulässige Abweichung permissible tolerance												
	zul. Abwei- chung	± 0,5						± 1,0			± 1,5		
		Gewichte in kg/m Weights in kg/m											
10	± 0,75	0,393	-	-	-	-	-	-	-	-	-	-	-
12		0,471	0,565	-	-	-	-	-	-	-	-	-	-
15		0,589	0,707	0,942	1,180	-	-	-	-	-	-	-	-
16		0,628	0,754	1,000	1,260	-	-	-	-	-	-	-	-
20		0,785	0,942	1,260	1,570	1,880	2,360	-	-	-	-	-	-
25		0,981	1,180	1,570	1,960	2,360	2,940	-	-	-	-	-	-
30		1,180	1,410	1,880	2,360	2,830	3,530	4,710	5,890	-	-	-	-
35		1,370	1,650	2,200	2,750	3,300	4,120	5,500	6,870	-	-	-	-
40	± 1,0	1,570	1,880	2,510	3,140	3,770	4,710	6,280	7,850	9,420	-	-	-
45		1,770	2,120	2,830	3,530	4,240	5,300	7,070	8,830	10,600	-	-	-
50		1,960	2,360	3,140	3,930	4,710	5,890	7,850	9,810	11,800	15,70	-	-
55		2,160	2,590	3,450	4,320	5,180	6,480	8,640	10,800	13,000	-	-	-
60		2,360	2,830	3,770	4,710	5,650	7,070	9,420	11,800	14,100	18,80	23,60	-
65		2,550	3,060	4,080	5,100	6,120	7,650	10,200	12,800	15,300	20,40	-	-
70		2,750	3,300	4,400	5,500	6,590	8,240	11,000	13,700	16,500	22,00	27,50	-
75		2,940	3,530	4,710	5,890	7,070	8,830	11,800	14,700	17,700	23,60	-	35,30
80	± 1,5	3,140	3,770	5,020	6,280	7,540	9,420	12,600	15,700	18,800	25,10	31,40	37,70
90		3,530	4,240	5,650	7,070	8,480	10,600	14,100	17,700	21,200	28,30	35,30	42,40
100		3,930	4,710	6,280	7,850	9,420	11,800	15,700	19,600	23,600	31,40	39,30	47,10
110	± 2,0	-	-	6,910	8,640	10,400	13,000	17,300	21,600	25,900	34,50	43,20	-
120		-	-	7,540	9,420	11,300	14,100	18,800	23,600	28,300	37,70	47,10	56,50
130	± 2,5	-	-	8,160	10,200	12,200	15,300	20,400	25,500	30,600	40,80	51,00	-
140		-	-	8,790	11,000	13,200	16,500	22,000	27,500	33,000	44,00	55,00	-
150		-	-	9,420	11,800	14,100	17,700	23,600	29,400	35,300	47,10	58,90	70,70